

CLASSIC MEDUNA PT 0W-30 LL III LA

Passenger car engine oil HC-Synthesis basic SAE 0W-30 low SAPS, among other things for vehicles with extended change intervals

Description

CLASSIC MEDUNA PT 0W-30 LL III LA is a synthetic low-friction engine oil for petrol and diesel car engines with or without turbocharging and direct injection. Minimization of friction, wear and fuel consumption, excellent cold starting properties. Extended oil change intervals as per manufacturer's instructions.

CLASSIC MEDUNA PT 0W-30 LL III LA extends the operational life of the diesel particulate filter by reducing the concentration of ash-forming particles in the exhaust gas. Reduces the release of harmful emissions into the environment. Offers increased safety due to continuously high protection of the engines. It achieves a high viscosity index because of its formulation with special base oils.

Application

CLASSIC MEDUNA PT 0W-30 LL III LA is an energy-saving engine oil for year-round use in modern petrol and diesel engines. **CLASSIC MEDUNA PT 0W-30 LL III LA** is for extended oil change intervals and extends the service life of the particle filter. The operating instructions of the automobile and engine manufacturers must be observed.

Properties

- excellent cold starting properties, even at low temperatures below -30°
- very stable and excellent viscosity behaviour and shear stability
- fuel savings under all operating conditions
- secure lubricant film at high operating temperatures
- neutrality towards sealants
- low evaporation, thereby low oil consumption

Product data

Properties	Unit	0W-30*
Density 15 °C	g/cm ³	0.842
Viscosity 40 °C	mm ² /s	59.0
Viscosity 100 °C	mm ² /s	11.7
Viscosity index		197
Pourpoint	°C	-48

* are average values and may vary in the framework of the standard.

Quality level

ACEA C3

API SN

Performance

VW 504.00/507.00

Fiat 9.55535-DS1

BMW Longlife-04

VW G 52545

Fiat 9.55535-GS1

Porsche C30

MB 229.31 / 229.51

Fiat 9.55535-S3