

CLASSIC MEDUNA PT 5W-30 C2/C3

Passenger car motor oil HC-synthetic based SAE 5W-30 Low SAPS for diesel and gasoline engines

Description

CLASSIC MEDUNA PT 5W-30 C2/C3 is a high-performance smooth-running engine oil, based on HC-synthetic base oils, for modern diesel and gasoline engines of the latest technology.

CLASSIC MEDUNA PT 5W-30 C2/C3 contributes to a low fuel economy by reducing emissions to Euro V to protect the environment.

Application

CLASSIC MEDUNA PT 5W-30 C2/C3 has been developed to protect environmentally friendly exhaust gas after treatment systems such as particulate filters and three-way catalytic converters. Pollutant emissions such as HC, NO_x, CO and particles are therefore reduced.

Properties

- developed to reduce pollutant emissions according to Euro V
- The exhaust aftertreatment systems are also protected in the long term thanks to the „Low SAPS“ formulation
- universally applicable for diesel and gasoline engines
- very good wear protection even under high load
- low oiling circulation times and shorter start times during cold start

Product Data

Properties	Unit	5W-30*
Density 15 °C	g/cm ³	0.852
Viscosity 40 °C	mm ² /s	70.8
Viscosity 100 °C	mm ² /s	11.9
Viscosity index		166
Pourpoint	°C	-45
Flashpoint (COC)	°C	220

* are average values and may vary in the framework of the standard.

Quality Level

ACEA C2/C3

API SN

Performance

BMW LONGLIFE-04

IVECO 18-1811 CLASSE SC1

VW 505.00/ 505.01

FIAT 9.55535-S1/-S3

MB 229.31/ 229.51/ 229.52

GM dexos2™

RENAULT RN17