

CLASSIC MEDUNA PT 5W-30 LL III LA

Car engine oil, based on HC synthesis SAE 5W-30 Low Ash, among others for vehicles with extended change intervals

Description

CLASSIC MEDUNA PT 5W-30 LL III LA is a high-performance smooth-running engine oil, based on HC synthetic base oils, for modern passenger car engines of the latest technology. Excellent cold start behavior ensures optimum lubricating reliability in the cold running phase. Extreme stress and high temperatures are safely controlled under all conditions. Due to the high fuel savings the **CLASSIC MEDUNA PT 5W-30 LL III LA** contributes to protecting the environment by reducing emissions.

Application

CLASSIC MEDUNA PT 5W-30 LL III LA was specially developed for engines of the VW group with extended service intervals (WIV) and is therefore suitable for oil change intervals of up to 30,000 km or 2 years.

CLASSIC MEDUNA PT 5W-30 LL III LA can also be used in other VW engines. The corresponding operating instructions must be observed. This particularly low-emission motor oil lasts espacially the function of the emission control systems of diesel engines over a very long term.

CLASSIC MEDUNA PT 5W-30 LL III LA meets the MB 229.51 and the MB 229.52 approval in addition to the MB 229.31 approval and can therefore also be used in Mercedes-Benz engines that require these specifications. This product is ideal for the optimization of varieties in car workshops and at companies with smaller and bigger passenger car fleets such as in taxi companies, car rental companies, company fleets, etc.

Product data

Properties	Unit	5W-30*
Density 15 °C	g/cm³	0.851
Viscosity 40 °C	mm²/s	64.5
Viscosity 100 °C	mm²/s	11.6
Viscosity index		177
Pourpoint	°C	-42
Flash Point (COC)	°C	230

*are average values and may vary within the framework of the standard.

Quality level

ACEA C2/C3 API SP / SN Plus

Performance

approved according to VW standard 504 00 and VW standard 507 00MB approval 229.51MB 229.52 / MB 229.31Porsche C30Opel OV0401547

VW 503 01 BMW Longlife-04