

CLASSIC MEDUNA UM 15W-40

Universal motor oil mineral oil based SAE 15W-40

Description

CLASSIC MEDUNA UM 15W-40 is a universal high-performance multigrade engine oil of the highest quality standard. It is suitable for all diesel and petrol engines in commercial vehicles and passenger cars (observe vehicle manufacturer instructions). It is recommended for use in urban and long-distance traffic vehicles, city busses, coaches and construction machines of all types. **CLASSIC MEDUNA UM 15W-40** also meets the specific requirements of certain vehicle transmissions. Observe the relevant manufacturer instructions.

Application

CLASSIC MEDUNA UM 15W-40 is a universal all-season oil for all naturally aspirated and turbocharged petrol and diesel engines under all operating conditions, including heavy-duty operation. It is particularly recommended for use in vehicles with prolonged oil change intervals. **CLASSIC MEDUNA UM 15W-40** is the ideal product for operators of mixed vehicles fleets.

Product data

Properties	Unit	15W-40 *
Density 15 °C	g/cm ³	0.887
Viscosity 40 °C	mm ² /s	102
Viscosity 100 °C	mm ² /s	13.7
Viscosity index		135
COC flash point	°C	220
Pour point	°C	-27

* are average values and may vary in the framework of the standard.

Quality level

API CG-4/SL
ACEA A3/B4

Performance

MB 229.1	MAN M 3275-1
MTU Type 2	Volvo VDS
VW 501.01/505.00	Mack EO-L
Allison C-4	